

# TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES

## #33-301 • 6mm FL • f/1.85

Our ultra-compact, TECHSPEC® UC Series Fixed Focal Length Lenses are designed to optimize performance, cost, and size without sacrificing quality or feel. Designed for pixels that are  $\leq 2.2\mu\text{m}$ , these lenses provide high levels of resolution ( $>200\text{ lp/mm}$ ) across the sensor and are compatible with all standard C-Mount cameras. TECHSPEC® UC Series Fixed Focal Length Lenses feature focus and iris adjustments, as well as recessed set screws, and are manufactured for use at typical machine vision working distances. While they are optimized for  $1/2.5''$  sensors, many focal lengths will work on sensors up to  $1/1.8''$ . The TECHSPEC® UC Series lenses are an outstanding option for use on all smaller format camera sensors, along with both short and long working distance applications, making them ideal for inspection, factory automation, biomedical devices, and a broad range of other applications.




<b>Focal Length:</b>	6mm
<b>Minimum Working Distance<sup>1</sup>:</b>	50mm
<b>Focus Range:</b>	50mm - $\infty$
<b>Length at Near Focus:</b>	40.9mm
<b>Length at Far Focus:</b>	40.3mm
<b>Filter Thread:</b>	M34 x 0.5
<b>Max. Sensor Format:</b>	$1/2''$
<b>Optimized Sensor Format:</b>	$1/2.5''$

<b>Camera Mount:</b>	C-Mount
<b>Aperture (f/#):</b>	f/1.85 - f/11
<b>Magnification Range:</b>	0X - 0.090X
<b>Distortion:</b>	<9.5% (on $1/2.5''$ sensor)
<b>Object Space NA:</b>	0.00775
<b>Number of Elements (Groups):</b>	9 (8)
<b>AR Coating:</b>	$1/4\lambda$ MgF <sub>2</sub>
<b>Weight:</b>	67g


Sensor Size	$1/4''$	$1/3''$	$1/2.5''$	$1/2''$	$1/1.8''$	$2/3''$	$1''$	$4/3''$
<b>Field of View<sup>2</sup></b>	38.8mm - 34.23°	51.8mm - 44.68°	62.54mm - 52.78°	71.38mm - 58.97°	NA	NA	NA	NA

1. From front of housing 2. Horizontal FOV on standard 4:3 sensor format. Min. W.D. - angular FOV at infinite conjugate

Specifications subject to change



**Figure 1:** Distortion at the maximum sensor format. Positive values correspond to pincushion distortion, negative values correspond to barrel distortion.



**Figure 2:** Relative illumination (center to corner)


In both plots, field points corresponding to the image circle of common sensor formats are included. Plots represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.

TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES


© COPYRIGHT 2014 EDMUND OPTICS, INC. ALL RIGHTS RESERVED

**TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES**  
**#33-301 • 6mm FL • f/1.85**

**MTF & DOF: f/1.85**  
**WD: 100mm**



**Figure 3:** Image space polychromatic diffraction FFT Modulation Transfer Function (MTF) for  $\lambda = 486\text{nm}$  to  $656\text{nm}$ . Included are Tangential and Sagittal values for field points on center, at 70% of full field and at the maximum sensor format. Solid black line indicates diffraction limit determined by  $f/\#$ -defined aperture. Frequencies corresponding to the Nyquist resolution limit of pixel sizes are indicated.




**Figure 4:** Polychromatic diffraction through-focus MTF at 20 linepairs/mm (image space). Contrast is plotted to two times the focus distance. Note object spatial frequency changes with working distance.


Plots represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.

**TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES**  
**#33-301 • 6mm FL • f/1.85**

**MTF & DOF: f/1.85**  
**WD: 200mm**



**Figure 5:** Image space polychromatic diffraction FFT Modulation Transfer Function (MTF) for  $\lambda = 486\text{nm}$  to  $656\text{nm}$ . Included are Tangential and Sagittal values for field points on center, at 70% of full field and at the maximum sensor format. Solid black line indicates diffraction limit determined by  $f/\#$ -defined aperture. Frequencies corresponding to the Nyquist resolution limit of pixel sizes are indicated.




**Figure 6:** Polychromatic diffraction through-focus MTF at 20 linepairs/mm (image space). Contrast is plotted to two times the focus distance. Note object spatial frequency changes with working distance.


Plots represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.

**TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES**  
**#33-301 • 6mm FL • f/1.85**

**MTF & DOF: f/4.0**  
**WD: 100mm**



**Figure 7:** Image space polychromatic diffraction FFT Modulation Transfer Function (MTF) for  $\lambda = 486\text{nm}$  to  $656\text{nm}$ . Included are Tangential and Sagittal values for field points on center, at 70% of full field and at the maximum sensor format. Solid black line indicates diffraction limit determined by  $f/\#$ -defined aperture. Frequencies corresponding to the Nyquist resolution limit of pixel sizes are indicated.




**Figure 8:** Polychromatic diffraction through-focus MTF at 20 linepairs/mm (image space). Contrast is plotted to two times the focus distance. Note object spatial frequency changes with working distance.

Plots represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.


**TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES**  
**#33-301 • 6mm FL • f/1.85**

**MTF & DOF: f/4.0**  
**WD: 200mm**

TECHSPEC® UC SERIES FIXED FOCAL LENGTH LENSES



**Figure 9:** Image space polychromatic diffraction FFT Modulation Transfer Function (MTF) for  $\lambda = 486\text{nm}$  to  $656\text{nm}$ . Included are Tangential and Sagittal values for field points on center, at 70% of full field and at the maximum sensor format. Solid black line indicates diffraction limit determined by  $f/\#$ -defined aperture. Frequencies corresponding to the Nyquist resolution limit of pixel sizes are indicated.



**Figure 10:** Polychromatic diffraction through-focus MTF at 20 linepairs/mm (image space). Contrast is plotted to two times the focus distance. Note object spatial frequency changes with working distance.

Plots represent theoretical values from lens design software. Actual lens performance varies due to manufacturing tolerances.